



RECEIVER-TONE ONLY PAGER

GUEST PAGING AL-A07



Rich Sophistication

- Tone, vibrate, and flashed (dual color LED) alert
- Over the air "off "
- 4 addresses (with four functions per address)
- Programable Alert type
- Two LED (Heartbeat, Alert, Out of range, Low battery)
- Ni-MH Rechargeable battery

Key Specifications

1. Large area for advertisement (45x 107 mm)
2. Tone / Vibration / Flash alert
3. For guest paging / Compact size
4. Highly recommend to use with Desktop transmitter
5. IP67approval
6. LCD Display (00~899 digits) with blue backlight
7. PC programmable

Specifications

Frequency	430~470 MHz
Paging Sensitivity	1200bps -- 7uV/M
Bit Rate	1200bps for POCSAG
Channel Spacing	12.5KHz / 25KHz
Code Format	POCSAG
Spurious Rejection	40db below carrier
Alert Tone Loudness	78db @ 10 cm
Capcodes	4 Capcodes for POCSAG
Dimension (mm)	135(L) x 63(W) x 18(H)
Weight (with battery)	127g

Charger



Australia

WiPath Communications Pty Ltd (ACN: 86 093 464 496)
 Postal: PO Box 446, Burwood 1805, Australia
 Street: L2, 5 Belmore St, Burwood, NSW 2134, Australia
 P: +61-2-9715 2238 F:+61-2-9715 2941 E:info@wipath.com.au

New Zealand

WiPath Communications Ltd
 Postal: PO Box 8798, Symonds St, Auckland 1150, NZ
 Street: 3/2 Haultain St, Eden Tce, Auckland, New Zealand
 P: +64-9-302 1142 F:+64-9-302 1148 E:info@wipath.co.nz

USA

WiPath Communications LLC
 4467 Terracemeadow Court, Moorpark, CA 93021
 P: +1-805-532 9964 F:+1-805-5298549
 E: info@wipath.com