



NEW ZEALAND
 WiPath Communications Ltd
 Postal: PO Box 8798, Symonds St, Auckland 1150, New Zealand
 Street: 3/2 Haultain St, Eden Tce, Auckland, New Zealand
 P: +64-9-302 1142 F: +64-9-302 1148 E: info@wipath.co.nz

AUSTRALIA
 WiPath Communications Pty Ltd
 Postal: PO Box 6947, Silverwater, NSW 2128, Australia
 Street: Unit 44, 8 Avenue of Americas, Newington, NSW 2127, Australia
 P: +61-2-8004 0535 F: +61-2-9647 1559 E: info@wipath.com.au

Apollo AL/AF-A25

Synthesised Pocsag & Crystalled FLEX Alphanumeric Pagers
 Robust, 4 button operation with left and right navigation
 Ideal for users who want a robust pager with easy operation and very good readability



Features

- Robust pager, 4 button operation with left & right navigation
- 4 line zoomable to 2 line display
- 84 character capacity 1 page display (4 line)
- 28,672 character capacity memory (Pocsag) & 30,000 (Flex) Personal messages
- 24,576 character capacity (Pocsag) & 27,000 (Flex) Maildrop messages
- 6 Capcode capacity (Pocsag) & 16 Capcode capacity (Flex) which can be Personal, Group or Maildrop with no frame restrictions
- Display source address number option
- Real Time Clock Calendar
- Time/Date stamp on messages
- 16 Personal memory slots, 5 lockable + 10 slots if message full, 5 memo slots & 10 each Maildrop slots
- Hand Programmable option
- 8 Melody Alerts, 4 Beep Alerts, Vibe & Sleep modes
- Alert & Vibe option
- 5 Daily Alarm sets
- Message preview of first 1 or 2 lines
- Instant message Display option
- 2, 8, 16, 32 second & continuous Personal alert options
- Nil, beep 1 & 16 second Maildrop alert options
- Priority Alert Override
- Delete All Function
- Auto Scroll function
- Auto Sleep function
- Duplicate Message indicator
- Unread message display & Reminder alert
- Blue Backlight with auto on, on receipt of message or manual push button options
- Extra long battery life
- Battery Level indicator and Low Battery alarm
- Option to disable functions: set scroll, pager off, set auto sleep, set alarm, set time & zoom in/out
- Suitable for Network or Local Area Paging
- 12 Month service warranty

Specifications

Model Codes/Protocols	Pocsag (ALA25) & Flex (AFA25)
Frequency	132-174 MHz, 443-473 MHz and, 929-931 MHz (AL924), 157.950 (AF924)
Paging Sensitivity	512 BPS-5uV/M, 1200 BPS-7uV/M, 2400bps-9uV/M
Baud Rate	512 / 1200 / 2400 BPS for POCSAG, 1600 / 3200 / 6400 BPS for FLEX
Spurious Rejection	40db below carrier
Channel Spacing	25 kHz
Selectivity	60db @ 25 kHz
Frequency Deviation	+/- 4.5 kHz
Alert Tone Loudness	85db @ 10 cm
Dimensions	Pager = 20 (h) x 78 (l) x 52mm (w). Display = 46 (l) x 17 mm (w)
Weight (with battery)	90g with battery & 120g with battery & holster
Battery	One 1.5 V AA Alkaline Battery