



NEW ZEALAND

WiPath Communications Ltd
 Postal: PO Box 8798, Symonds St, Auckland 1150, New Zealand
 Street: 3/2 Haultain St, Eden Tce, Auckland, New Zealand
 P: +64-9-302 1142 F: +64-9-302 1148 E: info@wipath.co.nz

AUSTRALIA

WiPath Communications Pty Ltd
 Postal: PO Box 6947, Silverwater, NSW 2128, Australia
 Street: Unit 44, 8 Avenue of Americas, Newington, NSW 2127, Australia
 P: +61-2-8004 0535 F: +61-2-9647 1559 E: info@wipath.com.au

Apollo Platinum XP

Narrowband & Wideband Programmable
 IP54 Approval for Water-resistance and Dust-tight



ALA29 (Pocsag)

Key Specifications & Special Features

1. Synthesized or Crystal Type
2. Loud Buzzer, Strong Vibrator
3. Blue Back-light, Large Display
4. 6 Keys Operation, User Friendly Interface
5. Selective PC or Hand Programmable
6. IP54 Approval for Water-resistance and Dust-tight
7. AAA Rechargeable Battery
8. Charger with relay output is optional
9. Support Languages: English, Spanish, Portuguese, Russian, German, and French

AL-A29 Rich Sophistication

- 4 Lines, Total 84 Alphanumeric One Page Display
- IP-54 Approval
- Blue Back-Light, Large Screen
- 6 Keys Operation, Easy Operation
- Use Rechargeable 2.4V 350mAh Battery
- Desk Charger (Optional)
- Large Memory Size; Total Capacity 259,062 Letters
- General Message: 16 sets + Message Full: 10 sets, total capacity 20480 letters
- Personal Message: 10 sets, total capacity 1000 letters
- Mail Drop: 15 sets, total capacity 228,345 letters
- 4 Beep Alerts with LED Flash, 10 Melody Alerts with LED Flash, Vibration with LED Flash, LED Flash Only, or Sleep
- 12hr or 24 hr format real time clock (selectable)
- Unread Message Reminder Alert
- Error Message, Duplicate Message, Full Message Indicator
- Manual pager on/off
- Convenient Functions; 5 Daily Alarm, Auto Scroll, Auto Sleep, Zoom In/Out
- 10 Sets for Messages Lock
- Real Time Clock Calendar
- Message Time Stamp
- Month, Date, Year, Time Display (British or American date format)
- 5 sets daily alarm
- Memory retention during battery replacement
- Page scrolling (selectable)
- Selective PC or Hand Programming
- Up to 8 Capcodes for POCASG

Specifications

Model Codes/Protocols	Pocsag (ALA29)	Selectivity	60db @ 25 kHz
Frequency	132-174 MHz (RoHS), 473 MHz and, 929-931 MHz (ALA29)	Frequency Deviation	+/- 4.5 kHz
Paging Sensitivity	512 BPS-5uV/M, 1200 BPS-7uV/M, 2400bps-9uV/M	Alert Tone Loudness	88dB @ 10 cm
Baud Rate	512 / 1200 / 2400 BPS for POCASG	Battery	1x 2.4V 350mA Rechargeable Battery
Dimensions	Pager: 22 (h) x 79 (l) x 57 mm (w). Display: 57 (l) x 20 mm (w)	Channel Spacing	25 kHz
Weight (with battery)	90g with battery & 130g with battery & holster	Spurious Rejection	40db below carrier