

AUSTRALIA

WiPath Communications Pty Ltd
Postal: PO Box 227 Chester Hill, NSW 2162, Australia
Street: Unit 13, 10 Straits Avenue, South Granville, NSW 2142, Australia
P: +61-2-8004 0535 F: +61-2-9681 4010 E: info@wipath.com.au

NEW ZEALAND

WiPath Communications Ltd
Postal: PO Box 8798, Symonds St, Auckland 1150, New Zealand
Street: 3/2 Haultain St, Eden Tce, Auckland, New Zealand
P: +64-9-302 1142 F: +64-9-302 1148 E: info@wipath.co.nz



AL-A06 UFO



Key Specifications/Special Features:

1. Synthesized or Crystal Type
2. Tone / Vibration / Flash (Dual Colour LED) pager
3. For guest paging / Compact size
4. PC Programmable
5. Highly recommend for use with Desktop transmitters
TE-300 / TE-310 / TE-205N
6. IP67 Water Resistant

AL-A06 Rich Sophistication:

- * Tone, vibrate, and flashed (dual colour LED) alert
- * Over the air "off "
- * 4 addresses (with four functions per address)
- * Programmable Alert type
- * Two LED (Heartbeat, Alert, Out of range, Low battery)
- * Ni-MH Rechargeable battery

Specifications:

Frequency	408~473Mhz UHF
Paging Sensitivity	512bps -- 5μV/M, 1200bps -- 7μV/M, 2400bps -- 9μV/M
Bit Rate	512 / 1200 / 2400bps for POCSAG
Channel Spacing	25Khz
Code Format	POCSAG
Spurious Rejection	40db below carrier
Alert Tone Loudness	80db @ 10 cm
Capcodes	4 Capcodes for POCSAG
Dimension	110 mm (Diameter) x 16.20 mm (H)
Weight	(with battery) Approximately: 110g